


## Order form - SCREEN

**Opoterm**, **top-mounted** box Standard system

Fart Produkt Ltd. Limited partnership, Towarowa street 3, 87-100 Toruń tel. +48 56 623 55 77, fax. +48 56 649 57 23, export@fartprodukt.pl, www.fartprodukt.pl









A – without building-over B – with building-over from within C

C - with total	building-over

	Cassette		Guidance						Kolor skrzynki					Fabrics				**			
<u>=</u>				es es				Bottom	Frontal profiles			Revision placement			*		Drive montage side		Туре		
Ordinal	170 [mm]	210 [mm]	240 [mm]	<b>ZIP</b> guidance	<b>Bottom beam</b> in side guides	Total width [mm]	Total height [mm]	Quantity [pcs.]	beam colour	External	al Internal	Revision flap colour	From the forehead	From under– neath	Colour of fabric	* * * * Back	Motor	(from	within)	of adaptive profile	
		61																			
Types of adaptive profiles:  PSAW/6,7/x  PSAW/6,8/x  PSAW/7,9/x  PSAW/8/x  PSAW/8/2/x  PSAW/8/2/x  PSAW/8/3  PSAW/8/3  PSAW/8/3  PSAW/8/2/x  PSAW/8/X  PSAW/8/2/x  PSAW/8/X  PSA											8										
light t As a s If you	light transmission properties. In the pattern, these fabrics are presented by 2 samples: "front" and "back". As a standard, the "front" of the fabric is on the outside of the building and the "back" is by the room side. If you want to "invert" the sides, please select the "back" option.									Order date Lead time				DIMENSIONING  By top mounted roller shutter, the width of the shield is equal to the width of the window frame.  To the height of the frame the height of appropriate roller shutter box should be added.							
COMN	COMMENTS / DRAWINGS FROM WITHIN							S	Stamp and signature of commissioning party								-	- wic	JUI -		