

Order form – SCREEN

Surface-mounting

Premium system

Fart Produkt Ltd. Limited partnership, Towarowa street 3, 87-100 Toruń tel. +48 56 623 55 77, fax. +48 56 649 57 23, export@fartprodukt.pl, www.fartprodukt.pl

TYPE OF CASSETTE MONTAGE *		TYPE (OF SIDE GUIDE MO	NTAGE ***	DRIVE MONTAGE SIDE **	OUTPUT OF DRIVE CABLE	****	MOONTING
	_			PVC			_	CLIP OF CASSETTE
A	В	FRONTAL	SIDE	MOUNTING	l L R	A - side	- B – back	
				CLIP				
		🛏 -	🗕 ,					[only
		∀			(view from within)	C – without hole		125 mm cassettes]
					(view from within)	C - without hole		*

			*		Guidano		****	ale ale ale ale	****		l				Canat	ruction				Fabrics				***			**		4	****							
lal	Cassette		Type of cassette				cassette		cassette		cassette		pe of		e e	Mounting clip of cassette [only 125 mm cassettes]	Total width	Total height	Quantity	9	-				Ş. L.	RAL rgé)	-	* *		pe of side	de		Dri mor si (from v	ive	l	t of driv	
Ordinal	4	5°	9	90°	moi	ntage	ZIP guidance	Bottom beam in side guides	ble si d	nting sette nm cas	[mm]	[mm]	[pcs.]	white RAL 9016	creme RAL 9001	silver RAL 9006	brown RAL 8014	anthracite RAL 7016	black gray RAL 7021	varnishing RAL (extra chargé)	Colour of fabric	*	lip e lip		Motor	(ITOITI WILIIII)											
	95 [mm]	125 [mm]	95 [mm]	125 [mm]	Α	В	<u>و</u>	Bott in si	ซื	Mou cas 125 m				^ ≵		₩.	R/	an R⁄	bls R4	varni (extr		Back	Frontal	Side	Pvc clip		L	R	A	В	С						

CAUTION. In some of the screen fabrics, the front and back side of the fabric differ in a light transmission properties. In the pattern, these fabrics are presented by 2 samples: "fro As a standard, the "front" of the fabric is on the outside of the building and the "back" is by	ont" and "back".		Transport
If you want to "invert" the sides, please select the "back" option.	*****		
		Order date	Lead time
COMMENTS / DRAWINGS FROM WITHIN		Stamp and signature of co	mmissioning party
			3/1

DIMENSIONING

By installation in a recess, the measurement should be taken in 3 places and the **smallest value** should be specified in the order.

Allowing for a slight mounting clearance should be taken into account.

