



## Order form - SCREEN


## Surface mounting


Standard system

Fart Produkt Ltd. Limited partnership, Towarowa street 3, 87-100 Toruń tel. +48 56 623 55 77, fax. +48 56 649 57 23, export@fartprodukt.pl, www.fartprodukt.pl









	Cassette		2	*		Guidance		Total width [mm]	Total height [mm]	Quantity [pcs.]	Construction colour (* – similar to colours with this number from the RAL palette)							Fabrics		Type of ***			**								
<u></u>				Type of cassette montage			am les				01 silver RAL 9006 08B dark-	, <b>*</b> 6	, L	*	~	22B ultra white 9016*	23B anthracite gray 7016* 34B quartz	7 *	۶	aluminium varnishing RAL (extra chargé)	Colour of fabric	* * *	side guide montage			mor si	Drive montage side (from within)		Output of drive cable		
Ordinal						<b>ZIP</b> guidance	m be					dark 1 801	brow	rème 900	20B black 9005*			quart 7039	37B gray aluminium						Motor	(from	within)				
		120 [mm]	Α	В	guic	Bottom beam in side guides				RAI	08B dark- brown 8019*	09B 8(	15 crème white 9001*	20B 90	22E white	23B a gray	gray 7016* 34B quartz gray 7039*	gray 37E alun	alun varnisl (extra		Back *	Frontal	Side		L	R	Α	В	С		

<b>CAUTION.</b> In some of the screen fabrics, the front and back side of the fabric differ in light transmission properties. In the pattern, these fabrics are presented by 2 samples: "As a standard, the "front" of the fabric is on the outside of the building and the "back" is the same of the building and the "back" is the same of the building and the same of the building and the "back" is the same of the building and the same of the building and the back.	front" and "back".	Order no	Transport			
If you want to "invert" the sides, please select the "back" option.	*****					
		Order date	Lead time			
COMMENTS / DRAWINGS FROM WITHIN	Stamp and signature of commissioning party					
			27			

## DIMENSIONING

By installation in a recess, the measurement should be taken in 3 places and the **smallest value** should be specified in the order.

Allowing for a slight mounting clearance should be taken into account.

